

Parameter	Value
Pixel Pitch	1.588mm
LED Type	3-in-1 SMD
Brightness	600cd/m² (nits)
Pixels Per Panel	384 x 216 pixels
Pixel Density	396,550pixels /m²
Weight	7kg (15.4lbs)
Module Size	W152.48mm×H171.54mm (6in x 6.8in)
Cabinet Size	W609.92mm×H343.08mm×D68mm (24in x 13.5in x 2.7in)
Aspect Ratio	16:9
Material	Die-cast Aluminum
Ingress Protection	Rear IP60
Curve	0°~+7°(Concave)
Operating Temperature/Humidity	-10°C~+45°C/ 10~80% RH
Storage Temperature/Humidity	-20°C~+55°C/ 10~85% RH
Standard Mounting	Fixed
Horizontal / Vertical Viewing Angle	160° / 160°
Color Temperature	2000-9500K Adjustable
Brightness Control	Manual/Automatic
Contrast Ratio	5000:1
Input Power (Max/Typical)	130W/43W per panel
Video Frame Rate	50/60 Hz
Refresh Rate	3840 Hz
Input Voltage	100~240VAC
Input Power Frequency	50~60 Hz
Mounting Configurations	Wall-mounting, Concave
Certifications	UL/FCC/IC/CE/CB/ROHS/CCC