Parameter	Value
Pixel Pitch	2.6mm
LED Type	3-in-1 Black SMD
LED Configuration	1Red,1Green,1Blue
Brightness	1000cd/m²
Pixels Per Panel	192×384 Dots
Pixel Density	147,456 pixels/m²
Weight	13 kg/panel
Module Size	W250mm×H250mm
Cabinet Size	W500mm×H1000mm×D83.3mm
Aspect Ratio	1:2
Area	0.5 m²
Recommended Viewing Distance	≥2.6 m
Material	Die-casting Aluminum
Environment	Indoor
Ingress Protection	IP30
Operating Temperature/Humidity	-10℃~+45℃/10~80%RH
Storage Temperature/Humidity	-20℃~+55℃/10~85%RH
Maintenance	Rear and Front
Horizontal Viewing Angle	140°
Vertical Viewing Angle	120°
Color Temperature	2000-9300K Adjustable
Colors	4.4 Trillion
Brightness Control	Manual/Automatic
Contrast Ratio	3000:1

Input Power <Max>	240W/panel
Input Power <Typical>	80W/panel
Driving Method	Constant Current Drive
Video Frame Rate	50/60 Hz
Rate Refresh	2880 Hz
Input Voltage	100~240VAC
Input Power Frequency	50~60 Hz
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video, etc
Calibration	Support brightness and chroma
Acoustic Noise	Fanless Design
LED Life Time	≥100,000 Hours
LED Wavelength	R:620~630nm G:520~535nm B:465~475nm
Standard Mounting Configuration	Fixed, Floor-mounted
Professional Services	Design, configuration, install and service available
Power Status	Diagnostic LEDs
Data Interconnection	Network Cable (L≤100m); multi-mode fiber (L≤300m); single mode fiber (L≤15km)