

Parameter	Value				
Model	Uslim II 1.5	Uslim II 1.8	Uslim II 2.5	Uslim II 3.2	Uslim II 3.9
Pixel Pitch	1.56mm	1.85mm	2.5mm	3.2mm	3.9mm
Pixel Density	409,600 dots/m²	291,600 dots/m²	160,000 dots/m²	97,344 dots/m²	65,536 dots/m²
Panel Resolution	320 x 160 dots	270 x 135 dots	200 x 100 dots	156 x 78 dots	128 x 64 dots
	320 x 320 dots	270 x 270 dots	200 x 200 dots	156 x 156 dots	128 x 128 dots
	320 x 640 dots	270 x 540 dots	200 x 400 dots	156 x 312 dots	128 x 256 dots
Panel Size (W × H × D)	500mm×250mm×39.6mm	500mm×250mm×39.6mm	500mm×250mm×39.6mm	500mm×250mm×39.6mm	500mm×250mm×39.6mm
	500mm×500mm×39.6mm	500mm×500mm×39.6mm	500mm×500mm×39.6mm	500mm×500mm×39.6mm	500mm×500mm×39.6mm
	500mm×1000mm×39.6mm	500mm×1000mm×39.6mm	500mm×1000mm×39.6mm	500mm×1000mm×39.6mm	500mm×1000mm×39.6mm
Material	Die-cast Aluminum	Die-cast Aluminum	Die-cast Aluminum	Die-cast Aluminum	Die-cast Aluminum
Brightness	1,000 cd/m²	1,000 cd/m²	1,000 cd/m²	1,000 cd/m²	1,000 cd/m²
Color Temperature	2,000 - 9,300 K Adjustable	2,000 - 9,300 K Adjustable	2,000 - 9,300 K Adjustable	2,000 - 9,300 K Adjustable	2,000 - 9,300 K Adjustable
Viewing Angle (H/V)	155°/155°	155°/155°	155°/155°	155°/155°	155°/155°
Panel Weight	3.2/5.6/10.5kg	3.2/5.6/10.5kg	3.2/5.6/10.5kg	3.2/5.6/10.5kg	3.2/5.6/10.5kg
Contrast Ratio	5,000 : 1	5,000 : 1	5,000 : 1	5,000 : 1	5,000 : 1
Service Access	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
Input Power (Max.)	538 W/m²	500 W/m²	440 W/m²	498 W/m²	450 W/m²
Input Power (Ave.)	179 W/ m²	167 W/m²	147 W/m²	166 W/m²	150 W/m²
Ingress Protection	IP30/IP10	IP30/IP10	IP30/IP10	IP30/IP10	IP30/IP10
Input Voltage	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC
Refresh Rate	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz
Operating Temperature /Humidity	-10°C to 45°C/ 10% - 80% RH	-10°C to 45°C/ 10% - 80% RH	-10°C to 45°C/ 10% - 80% RH	-10°C to 45°C/ 10% - 80% RH	-10°C to 45°C/ 10% - 80% RH
Storage Temperature /Humidity	-20°C to 55°C/ 10% - 85% RH	-20°C to 55°C/ 10% - 85% RH	-20°C to 55°C/ 10% - 85% RH	-20°C to 55°C/ 10% - 85% RH	-20°C to 55°C/ 10% - 85% RH